

CAMERA SYSTEMS

Dash Cam

Work Lights

Reversing Aids

CCTV Asset Tracking

VT9WQDVR

High quailty industrial class wireless camera & monitor.

Designed for operator safety and effiency in the material handling industry.

Frequency hopping technology ensures an interfarence free image at all time.

Now features real time transmission with virtualy no delay.

Add up to four cameras.

- logistics
- agriculture
- transport
- marine
- forklift
- bus & coach
- mining & construction

Viewtech 7" Forklift Camera & Monitor Kit



Features

- Four wireless video inputs displayable simultaneously in split, quad etc
- high resolution digital monitor with daytime brightness and auto dimming for low light
- Split screen trigger wire
- 10V-32V dynamic voltage input range on monitor and camera
- High quality shock resistant construction
- shatter proof to 2.83G
- auto dimming LCD
- built in SD card recorder, can record 1, 2 or four cameras simultaneously.
- supports up to 128GB micro SD card for up to 220 hours recording





Specifications

water / dust rating	IP69K	
Resolution	800 x 480 7" Viewable monitor	
Audio	Yes	
Night Vision	5m (smart IR)	
Input Voltage	12V-36V on camera and monitor	
Viewing Angle	0.0 Lux with IR on	

DVR Advantages

- review events, accidents and near misses
- replay for training
- improved operator awareness
- procedure reviewing

Optional Wireless Cameras



- Model: VT671-69
- Features a Narrow 69° view
- 10V-32V



viewtech.co.nz



- Features a Narrow 45° view
- strong magnetic base
- 600mm antenna lead
- 10V-32V



VT7WQDVR PAGE 2

Accessories



Contourable dash/ windshield mount included



Clamp Mount (optional)



Overhead Bracket (optional)



Magnetic Camera Base (optional)

Wireless Range

The Viewtech monitor comes with two di-pole style antennas in order to maximise signal quailty and range. In some situations directional signalling may be required. In these situations additional antennas can be added to the system. These comes with leads so that the antenna can be mounted outside the cab etc.



12dBi Directional range booster. Comes with 2m RF lead.



18dBi Directional range booster. Comes with 2m RF lead.

Playback & DVR

The DVR system creates standard AVI files which can be played back on any PC or MAC. Files are time and date stamped and can be easily shared, copied and emailed. The system can accept up to 128GB micro sd cards and once full it simply starts to overwrite itself. You will always have a rolling period of time which can be reviewed. (see record times below)

Record Times

Mode / Card Size	8GB	16GB	32GB	64GB	128GB
Single 640 x 480	14h	28h	55h	110h	220h
Quad 320 x 240 (x4	11h	22h	43h	86h	172h
Split 400 x 480 (x2)	13h	25h	50h	101h	201h

